

## SPECIFICATION FOR APPROVAL

|                           |   |                                |
|---------------------------|---|--------------------------------|
| CUSTOMER                  | : |                                |
| PRODUCT TYPE              | : | SMD SEAM SEALING X'TAL 3.2×2.5 |
| NOMINAL FREQ.             | : | 16.000000MHz                   |
| TXC P/N                   | : | 7M16000032                     |
| REVISION                  | : | A2                             |
| CUSTOMER P/N              | : |                                |
| PM / SALES                | : |                                |
| DATE                      | : |                                |
| CUSTOMER SIGNATURE & Date |   |                                |

- (1) TXC requires one copy returned with signature and title of authorized individual that signifies acceptance of the attached specifications.
- (2) Orders received and accepted by TXC after return of signed copy of specification will be produced per these specifications.
- (3) Any changes to these specifications must be agreed upon by both parties and new revision of the Product Specification Sheet will be issued.
- (4) Any issuance of purchase order prior to consigning back the Approval page of "Specification Sheets" from customers will be regarded as the agreement on the contents of these specifications.

**MSL:Level 1**  
**RoHS Compliant**



# PRODUCT SPECIFICATION SHEET

PRODUCT TYPE : SMD SEAM SEALING X'TAL 3.2×2.5

NOMINAL FREQ. : 16.000000MHz

TXC P/N : 7M16000032

REVISION : A2

| PE/RD                                                                               | QA                                                                                  | MFG                                                                                  |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
|  |  |  |
| 11-Oct-11                                                                           | 11-Oct-11                                                                           | 11-Oct-11                                                                            |

**NOTE:**

- (1)Lead Free Products are "Directive 2002/95/EC of The European Parliament of 27 January 2003 on the restriction of the use of certain hazardous substances (RoHS) in electrical and electronic equipment" Compliant (Attachment: SGS Test Report).
- (2)Revision "Sx" is for engineering samples only. PE/RD's approval required.
- (3)Revision "Ax" is production ready. PE, QA and MFG's approval required

**MSL:Level 1**  
**RoHS Compliant**



| <u>Rev</u> | <u>Revise page</u> | <u>Revise contents</u>                               | <u>Date</u> | <u>Ref.No.</u> | <u>Reviser</u> |
|------------|--------------------|------------------------------------------------------|-------------|----------------|----------------|
| S1         | N/A                | Initial released                                     | 6-Jan-11    | N/A            | Xiaoyan Jiang  |
| A1         | N/A                | S Turn A                                             | 25-Jan-11   | N/A            | Xiaoyan Jiang  |
| A2         | 7                  | Change Label A& Label B,<br>Deleted Label C "G" Mark | 11-Oct-11   | ECR-11N092802  | Xiaoyan Jiang  |
|            |                    |                                                      |             |                |                |
|            |                    |                                                      |             |                |                |
|            |                    |                                                      |             |                |                |
|            |                    |                                                      |             |                |                |
|            |                    |                                                      |             |                |                |
|            |                    |                                                      |             |                |                |
|            |                    |                                                      |             |                |                |
|            |                    |                                                      |             |                |                |
|            |                    |                                                      |             |                |                |
|            |                    |                                                      |             |                |                |
|            |                    |                                                      |             |                |                |
|            |                    |                                                      |             |                |                |
|            |                    |                                                      |             |                |                |
|            |                    |                                                      |             |                |                |
|            |                    |                                                      |             |                |                |
|            |                    |                                                      |             |                |                |
|            |                    |                                                      |             |                |                |
|            |                    |                                                      |             |                |                |

## Spec Sheet Contents

| No. | Content                                           | Page  |
|-----|---------------------------------------------------|-------|
| 1   | ELECTRICAL SPECIFICATIONS                         | P.3   |
| 2   | FACTORY LOCATION                                  | P.3   |
| 3   | DIMENSIONS                                        | P.4   |
| 4   | MARKING                                           | P.4   |
| 5   | SUGGESTED REFLOW PROFILE& MANUAL SOLDER CONDITION | P.4   |
| 6   | STRUCTURE ILLUSTRATION                            | P.5   |
| 7   | EMBOSS CARRIER TAPE & REEL                        | P.6   |
| 8   | PACKING                                           | P.7   |
| 9   | RELIABILITY SPECIFICATIONS                        | P.8~9 |

## ■ ELECTRICAL SPECIFICATIONS

### Standard atmospheric conditions

Unless otherwise specified, the standard range of atmospheric conditions for making measurement and tests are as follow:

Ambient temperature : 25±5℃  
Relative humidity : 40%~70%

If there is any doubt about the results, measurement shall be made within the following limits:

Ambient temperature : 25±3℃  
Relative humidity : 40%~70%

### Measure equipment

Electrical characteristics measured by S&A250B or equivalent.

### Crystal cutting type

The crystal is using AT CUT (thickness shear mode).

### Unit Weight:

0.018±0.001 g/pcs


|    | Parameters                          | SYM.           | Electrical Spec. |      |     |        | Notes                                       |
|----|-------------------------------------|----------------|------------------|------|-----|--------|---------------------------------------------|
|    |                                     |                | MIN              | TYPE | MAX | UNITS  |                                             |
| 1  | Nominal Frequency                   | FL             | 16.000000        |      |     | MHz    | -                                           |
| 2  | Oscillation Mode                    | -              | Fundamental      |      |     | -      | -                                           |
| 3  | Load Capacitance                    | CL             | 12               |      |     | pF     | -                                           |
| 4  | Frequency Tolerance                 | -              | ±10              |      |     | ppm    | at 25 °C ± 3 °C                             |
| 5  | Frequency Stability                 | -              | ±18              |      |     | ppm    | Over Operating Temp. Range (Reference 25°C) |
| 6  | Operating Temperature               | -              | -0               | ~    | 85  | ℃      | -                                           |
| 7  | Aging                               | -              | ±2               |      |     | ppm    | 1st Year                                    |
| 8  | Drive Level                         | DL             | -                | -    | 200 | μW     | -                                           |
| 9  | Effective Resistance R <sub>r</sub> | R <sub>r</sub> | -                | -    | 60  | Ω      | -                                           |
| 10 | Shunt Capacitance C <sub>0</sub>    | C <sub>0</sub> | 0.0              | -    | 2.0 | pF     | -                                           |
| 11 | Motional Capacitance C <sub>1</sub> | C <sub>1</sub> | 0.0              | 1.7  | 5.0 | fF     | -                                           |
| 12 | Pulling Sensivity                   | TS             | 3.0              | 6.0  | 9.0 | ppm/pF | -                                           |
| 13 | Insulation Resistance               | -              | 500              | -    | -   | MΩ     | at DC 100V                                  |
| 14 | Storage Temperature Range           | -              | -40              | ~    | 85  | ℃      | -                                           |

## ■ FACTORY LOCATION

TXC (NINGBO) CORPORATION  
NO.189 Huang Shan West Road, Beilun District,  
Ningbo Zhejiang China


## DIMENSIONS

(Unit:mm)



\*Coplanarity of solderable areas Camber 0.10 mm Max

## MARKING



### Date Code:

| YEAR |      |      |      | MONTH |     |     |     |     |     |     |     |     |     |     |     |
|------|------|------|------|-------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
|      |      |      |      | JAN   | FEB | MAR | APR | MAY | JUN | JUL | AUG | SEP | OCT | NOV | DEC |
| 2005 | 2009 | 2013 | 2017 | A     | B   | C   | D   | E   | F   | G   | H   | J   | K   | L   | M   |
| 2006 | 2010 | 2014 | 2018 | N     | P   | Q   | R   | S   | T   | U   | V   | W   | X   | Y   | Z   |
| 2007 | 2011 | 2015 | 2019 | a     | b   | c   | d   | e   | f   | g   | h   | j   | k   | l   | m   |
| 2008 | 2012 | 2016 | 2020 | n     | p   | q   | r   | s   | t   | u   | v   | w   | x   | y   | z   |

\*This date code will be cycled every four years

## SUGGESTED REFLOW PROFILE

Solder melting point :220±10 °C, 60 sec. Min.


Peak Temperature: 260 ± 5 °C, 10 sec. Max.

## SUGGESTED MANUAL SOLDER CONDITION


Temperature: 350 ± 10 °C

Time: 3 sec.

Re-solder times: twice




■ STRUCTURE ILLUSTRATION





| NO | COMPONENTS          | MATERIALS                                                           | FINISH/SPECIFICATIONS                             |
|----|---------------------|---------------------------------------------------------------------|---------------------------------------------------|
| 1  | Cap                 | Kovar (Fe/Co/Ni)                                                    | -                                                 |
| 2  | Package             | Ceramic (Al <sub>2</sub> O <sub>3</sub> ) + Kovar (Fe/Co/Ni)+ Ag/Cu | -                                                 |
| 3  | PAD                 | Au                                                                  | Tungsten metalize<br>+ Ni plating<br>+ Au plating |
| 4  | Crystal blank       | SiO <sub>2</sub>                                                    | -                                                 |
| 5  | Conductive adhesive | Resin+Ag                                                            | -                                                 |
| 6  | Electrode           | Noble Metal                                                         | -                                                 |

# EMBOSS CARRIER TAPE & REEL



| DIMENSIONS | A         | B         | C         | D         | E         | F         | G         | H         |             |
|------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-------------|
|            | 1.65±0.10 | 3.40±0.10 | 2.70±0.10 | 4.00±0.10 | 8.00±0.20 | 4.00±0.10 | 1.55±0.10 | 1.75±0.10 | (UNIT : mm) |

## REMARK :



| DIMENSIONS | L        | L1      | W         | W1     |             |
|------------|----------|---------|-----------|--------|-------------|
|            | 178±1.00 | 13±0.50 | 11.5±0.20 | 8±0.10 | (UNIT : mm) |


■ **PACKING**

Reel Quantity :

1. Reel X 6 (6 Reels)
2. Reel X 12 (12 Reels)
3. Reel X 25 (12 Reels + 13 Reels)
4. Reel X 50 ( 12 Reelsx2 + 13 Reelsx2 )

Box Size:

1. L200 X W200 X H140mm
2. L200 X W200 X H250mm
3. L400 X W200 X H250mm
4. L400 X W400 X H280mm



(Label A) Size:100 X 100mm

|                                                                               |  |
|-------------------------------------------------------------------------------|--|
| <b>TXC</b>                                                                    |  |
| Inv No: 00096815                                                              |  |
| Po No: 21106326- 24- 1                                                        |  |
| Part No: <span style="border: 1px solid black; padding: 2px;">00000000</span> |  |
| Qty: 40000 PCS                                                                |  |
| C/No: 157- 44                                                                 |  |

(Label B) Size:80 X 40mm

|                                                                                 |                                                                       |            |
|---------------------------------------------------------------------------------|-----------------------------------------------------------------------|------------|
| TXC CORPORATION                                                                 |                                                                       | QA PASS    |
| DATE CODE: <span style="border: 1px solid black; padding: 2px;">00000000</span> | QTY: <span style="border: 1px solid black; padding: 2px;">0000</span> | 2011/09/02 |
| LOT NO: <span style="border: 1px solid black; padding: 2px;">00000000</span>    | <b>RoHS</b>                                                           |            |
| PART NO: <span style="border: 1px solid black; padding: 2px;">00000000</span>   | <b>HF</b>                                                             |            |
| FREQ: <span style="border: 1px solid black; padding: 2px;">00000000</span>      |                                                                       |            |

**[STORAGE]**

- 1.The storage time to be 1 year maximum.
- 2.Don't be caught in the rain.
- 3.The storage environment shall be 5℃ ~40℃ temperature and 30% ~ 75%RH humidity and free from the sun shine.
- 4.If customers have special requirements, we can paste labels according to it.