



# SPECIFICATION FOR APPROVAL

CUSTOMER : \_\_\_\_\_

PRODUCT TYPE : SMD SEAM SEALING X'TAL 3.2\*2.5

NOMINAL FREQ. : 27.120000MHz

TXC P/N : 7M27100019

REVISION : A1

CUSTOMER P/N : \_\_\_\_\_

PM / SALES : \_\_\_\_\_

DATE : \_\_\_\_\_

CUSTOMER SIGNATURE & Date

\_\_\_\_\_

\_\_\_\_\_

- (1) TXC requires one copy returned with signature and title of authorized individual that signifies acceptance of the attached specifications.
- (2) Orders received and accepted by TXC after return of signed copy of specification will be produced per these specifications.
- (3) Any changes to these specifications must be agreed upon by both parties and new revision of the Product Specification Sheet will be issued.

Attachment: Product Specification Sheet

- 1
- 2
- 3
- 4
- 5

**RoHS Compliant**

# PRODUCT SPECIFICATION SHEET

PRODUCT TYPE : SMD SEAM SEALING X'TAL 3.2\*2.5

---

NOMINAL FREQ. : 27.120000MHz

---

TXC P/N : 7M27100019

---

REVISION : A1

---

PE/RD	QA	MFG
		
28-Jun-05	5-Jul-05	30-Jun-05

**NOTE:**

- (1)Lead Free Products are "Directive 2002/95/EC of The European Parliament of 27 January 2003 on the restriction of the use of certain hazardous substances (RoHS) in electrical and electronic equipment" Compliant (Attachment: SGS Test Report).
- (2)Revision "Sx" is for engineering samples only. PE/RD's approval required.
- (3)Revision "Ax" is production ready. PE, QA and MFG's approval required

**RoHS Compliant**



**ELECTRICAL SPECIFICATIONS**

**Standard atmospheric conditions**

Unless otherwise specified, the standard range of atmospheric conditions for making measurement and tests are as follow:

- Ambient temperature : 22±5
- Relative humidity : 40%~70%

If there is no doubt about the results, measurement shall be made within the following limits:

- Ambient temperature : 22±1
- Relative humidity : 40%~70%

**Measure equipment**

Electrical characteristics measured by HP E5100A or equivalent.

**Crystal cutting type**

The crystal is using AT CUT (thickness shear mode).



**Unit Weight:**

0.018±0.001 g/pcs


	Parameters	SYM.	Electrical Spec.				Notes
			MIN	TYPE	MAX	UNITS	
1	Nominal Frequency	FL	27.120000			MHZ	-
2	Oscillation Mode	-	Fundamental			-	-
3	Load Capacitance	CL	12			pF	-
4	Frequency Tolerance	-	±30			ppm	at 25 ± 3
5	Frequency Tolerance	-	±30			ppm	Over Operating Temp. Range (Reference 25 )
6	Operating Temperature	-	-20	~	70		-
7	Aging	-	±3			ppm	1st Year
8	Drive Level	DL	-	10	-	uW	-
9	Effective Resistance Rr	Rr	-	-	60	Ω	-
10	Shunt Capacitance C0	C0	-	-	5	pF	-
11	Motional Capacitance C1	C1	-	-	NA	fF	-
12	Insulation Resistance	-	500	-	-	MΩ	at DC 100V
13	Storage Temperature Range	-	-40	~	85		-

**DIMENSIONS**

- 1. Crystal enclosure seal : Seam Weld
- 2. Crystal enclosure medium : Vacuum



**MARKING**




**Date Code**

YEAR \ MONTH					JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
					A	B	C	D	E	F	G	H	J	K	L	M
2001	2005	2009	2013	2017	N	P	Q	R	S	T	U	V	W	X	Y	Z
2002	2006	2010	2014	2018	a	b	c	d	e	f	g	h	j	k	l	m
2003	2007	2011	2015	2019	n	p	q	r	s	t	u	v	w	x	y	z
2004	2008	2012	2016	2020												


This date code will be cycled every four years

**SUGGESTED REFLOW PROFILE**

Total time : 200 sec. Max.  
Solder melting point :220




**STRUCTURE ILLUSTRATION**





NO	COMPONENTS	MATERIALS	QTY	FINISH/SPECIFICATIONS
1	Cap	Metal (Fe)	1	-
2	Base	Ceramic	1	Color black
3	PAD	Au	4	Tungsten metalize + Ni plating + Au plating
4	Crystal blank	SiO2	1	-
5	Conductive adhesive	Ag	4	Epoxy resin
6	Electrode	Ag + Cr	2	-

**PACKING : (EIA-481-2)**



DIMENSIONS	A	B	C	D	E	F	G	H	(UNIT : mm)
	1.40	3.40	2.70	4.00	8.00	4.00	1.50	1.75	

REMARK :



DIMENSIONS	L	L1	W	W1	pcs / Reel (UNIT : mm)
	178	13	11.5	8	Standard Reel Quantity is 3,000 pcs per reel

**RELIABILITY SPECIFICATIONS**

No.	Test Item	Test Methods	REF.DOC
1	Drop Test	150 cm height, fall freely onto stainless plate 3 times.	
2	Mechanical Shock	Device are shocked to half sine wave ( 1000 G ) three mutually pendicular axes each 3 times. 0.5m sec. duration time	
3	Vibration	Frequency range                      10 ~ 2000 Hz Amplitude                                      1.52 mm Sweep time                                      20 minute Pendicular axes each test time              4 hours (Total test time 12 hours)	MIL-STD-883E
4	Solderability	Temperature                                      255 ± 5 Immersing depth                                      0.5 mm minimum Immersion time                                      10 ± 0.5 seconds Flux    Rosin resin methyl alcohol solvent ( 1 : 4 )	MIL-STD-883E
5	Resistance To Soldering Heat	Pre-heat temperature                                      125 Pre-heat time    60 ~ 120 sec. Test temperature    260 ± 5 Test time    5 ± 1 sec.	MIL-STD-202F
6	High Temp. Storage	+ 125 ± 3 for 5000 ± 12 hours	JIS C 0021
7	Low Temp. Storage	- 40 ± 3 for 500 ± 12 hours	JIS C 0020
8	Thermal Cycles	Total 100 cycles of the following temperature cycle  <p>The diagram illustrates a single thermal cycle. The temperature starts at 125 ± 3, drops to -55 ± 3, dwells for 30 minutes, rises back to 125 ± 3, dwells for 30 minutes, and then transitions back to the starting temperature. The transition times are limited to a maximum of 10 minutes. The entire cycle is repeated 100 times.</p>	